

12331 S.W. 130 STREET
MIAMI, FLORIDA 33186
(305) 238-4373



NILES AUDIO CORPORATION

**LVW-1
WALL-MOUNT
LINE-LEVEL VOLUME ATTENUATOR**

INTRODUCTION

There are installations where the use of a high-power volume attenuator such as our SCW-1 is not applicable. This would be the case if a single source was used to drive multiple power amplifiers. You would want to be able to attenuate the LINE-LEVEL-SIGNAL going INTO each amplifier. The LVW-1 was designed to do just that! The LVW-1 is a wall-mount stereo line-level attenuator and has a nominal input impedance of 100k ohms. The left and right channels are totally isolated. Therefore, the control will in no way contribute to any ground loops.

INSTALLATION

The LVW-1 installs in a single gang box mount electrical wall box. You must specify a box with a depth of approximately 3 inches since the unit itself extends 2 1/2" behind the front panel. Make sure to terminate your audio signal cables with male RCA type connectors. Plug the cables originating from the preamp (or other source unit) into the LEFT IN and RIGHT IN connections. Plug the cables that will go to the power amp into the LEFT OUT and RIGHT OUT connections.

OPERATION

To operate, simply rotate the control knob clockwise for louder and counter-clockwise for softer.

SPECIFICATIONS

- LEVEL CONTROL IMPEDANCE: 100K OHMS
- CONNECTORS: RCA TYPE PHONO JACKS
- PLATE SIZE: 2 3/4" W X 4 1/2" H
- MOUNTING DEPTH: 2 1/2" MINIMUM

